



Pro Series

Gooseneck Highboy Trailer 30,000lb-45,000lb GVW

Ordered By: _____

Dealer: _____

PO#: _____

Date: _____

Standard Features:

Coupler:	Adjustable GN Ball Coupler	Lace Rail:	Channel - 6" w/Pockets & Rubrail
Safety Chains:	3/8" Grade 70 w/Grab Hooks	Cmembers:	Channel - 3" on 16" Centers
Width:	102" Overall	Wiring:	Arctic Wiring, Soldered & Enclosed in Conduit
Deck Height:	38"	Lights:	LED, Rubber Mounted (30' + c/w Side Signal)
Axles:	Electric Brakes, Grease Hubs, 8 Stud	Decking:	Spruce - 2" Treated
Suspension:	Rubber Bushing Leaf Springs w/Equalizers	Toolbox:	TB4 Riser Toolbox (upright)
Tires & Rims	16 Ply Tires w/ Dual Rims	Steps:	Each Side w/Grab Handles
Main Frame:	Wide Flange Beam (See Below)	Finish:	Sand Blast, Prime, Paint w/PPG Urethane

MODEL:

Quantity:

****NOTE** Only one type of trailer per order form.**

Select Model	Main Frame	Axle Size	Tire & Rim	Tare Weight	Carrying Capacity	Landing Gear
GHB318-24	12@19lb	2:15000lb	215/75R17.5	7074lb	30426lb	2:12000lb
GHB318-26	12@19lb	2:15000lb	215/75R17.5	7358lb	30142lb	2:12000lb
GHB318-28	12@19lb	2:15000lb	215/75R17.5	7658lb	29842lb	2:12000lb
GHB318-30	12@22lb	2:15000lb	215/75R17.5	7950lb	29550lb	2:12000lb
GHB318-32	12@22lb	2:15000lb	215/75R17.5	8258lb	29242lb	2:12000lb
GHB318-34	12@22lb	2:15000lb	215/75R17.5	8566lb	28934lb	2:12000lb
GHB318-36	12@22lb	2:15000lb	215/75R17.5	8874lb	28626lb	2:12000lb
GHB318-38	12@22lb	2:15000lb	215/75R17.5	9182lb	28318lb	2:12000lb
GHB318-40	12@22lb	2:15000lb	215/75R17.5	9490lb	28010lb	2:12000lb

OPTIONS:

215HS =	2-15000Lb Hyd/Spr	R7HD =	7' HD Slide In Ramps
315ES =	3-15000Lb Elec/Spr	R7 =	7' Slide In Ramps
315HS =	3-15000Lb Hyd/Spr	BT7 =	5' BT Conquer Ramps, F Width/Spr Asst
	<i>(Triple Axle Requires F2 Beam Upgrade)</i>	PS1 =	Pipe Spools (Between Pockets)
SS2 =	HDSS Suspension (10k+)	W4 =	Weld on 3 Bar Winch
SS3 =	HDSS suspension (10k+ tridem)	W4S =	Sliding 3 Bar Winch
SP10 =	Spare-ST215/75R17.5-16ply-dual	SWT =	Sliding Winch Track
USP8 =	ST235/75R17.5-18ply-dual-upgrade	W4P =	Removable 3 Bar Winch
SP8 =	Spare-ST235/75R17.5-18ply-dual	R4W =	Weld on - 4" D Ring
J3 =	2-12k 2spd	R4R =	Removable 4" D Ring
J5 =	2-25k 2spd	PS =	Pocket Stakes 13"
JH2T =	2-hyd Jacks w/o Power Pack	P4X =	4ea Extra Stake Pockets
GKP =	GN King Pin	P1X =	Additional-Stake Pockets
GB3 =	GN Ball 3"	TB2A =	36" Side Mount Toolbox
NR4 =	Raise Neck 4"	TB6 =	48" Side Mount Toolbox
UD =	Upper Deck 102" X 96"	DR1 =	8' Dunnage Rack
WM1 =	Winch Mount (Plate)	PDA =	Double A Red
W17 =	17.5K Winch Pkg c/w Battery	PG =	Charcoal Grey

