

## Quad Sport Trailer 3,500lb-5,000lb GVW

Ordered By:	1 By:		Dealer:			
PO#:			Date:			
Standard Feat						
Coupler:	2" A Frame Coupler			Angle Iron - 2" on 24" Centers		
Safety Chains:	1/4" Grade 70 w/Grab Hooks		Pockets:	Preformed - 3/16", no rub rail		
Width:	See below		Wiring:	Arctic Wiring, Soldered & Enclosed in Conduit		
Deck Height:			Lights:	LED, Rubber Mounted		
Axles:	Idler, Grease Hubs, 5 Stud		Decking:	Spruce - 2" Treated		
Suspension:	Double Eye 4 Leaf		Finish:	Sand Blast, Prime, Paint w/PPG Urethane		
Tires & Rims:	8 Ply Tires w/Modular Rims		Ramp:	5' slide in ramps		
Main Frame:	Channel - 4"		Fenders:	14 ga Tread Plate		
Rear Stabilizers:	Not Inlcuded					
MODEL:						
Quantity:	**NOTE**		Only one type of trailer per o		order form.	
Select Model	Main Frame	Axle Size	Tire & Rim	Tare Weight	Carrying Capacity	Landing Gear
EQS36-12	4" Channel	1:3500lb	205/75R15	1274lb	2,615lbs	1:2000lb
EQS37-14	4" Channel	1:3500lb	205/75R15	1479lb	2,410lbs	1:2000lb
<b>OPTIONS:</b>					, ,	
150IS =	1:5000Lb Idler/Spr		R3W =	Weld on 3"D ring		
	1:5000Lb Elec/Spr			Weld on 4" D ring		
EZ =	EZ Lube Hubs (pr/axle)		R3R =	Removable 3" D ring		
SP1 =	Spare-205/75R15-8ply (3500Lb)		R4R =	Removable 4" D ring		
SP2 =	Spare-ST225/7	5R15-8ply (5000Lb)	P4X =	4ea extra stake pockets		
AW1 =	Alum wheel upgrade-15"		P1X =	Additional-Stake Pockets		
ABM =	2 5/16" Adjustable Coupler		PDA =	Double A Red		
APR =	Adjustable pintle ring		PG =	Charcoal Grey		
TR1 =	Tubing rail-24"		ERR =	Add Rub Rail to Excel		
WER =	Weed Eater Rack		RS1 =	Rear Stabilizers (Tube)		
G4A =	4' ramp gate/sp	r asst		Document Holder		
Notes:						
10103.						
					Signature:	